

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 April 2002 (04.04.2002)

PCT

(10) International Publication Number
WO 02/26196 A1

- (51) International Patent Classification⁷: **A61K 6/00**, 6/083, 6/02
- (21) International Application Number: PCT/US01/42120
- (22) International Filing Date:
10 September 2001 (10.09.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/235,407 26 September 2000 (26.09.2000) US
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicants and
- (72) Inventors: **PATACCA, Thomas, R.** [US/US]; 6326 Latonia Road, Independence, OH 44131 (US). **PATACCA, Gregory, G.** [US/US]; 6798 Meadowbrook Boulevard, Independence, OH 44131 (US). **FRATE, Dean, M.** [US/US]; 3675 West 135th Street, Cleveland, OH 44111 (US).
- (74) Agent: **MOXON, George, W., II**; Brouse McDowell, 500 First National Tower, Akron, OH 44308-1471 (US).
- Published:**
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: TOOTH COATING COMPOSITION

(57) Abstract: A film forming composition for coating teeth which is a mixture of about 0.5 % to about 30 % by weight of a film forming polymer; about 10 % to about 99.5 % by weight of solvent; about 0.05 % to about 40 % by weight of a rheology modifier; about 0.01 % to about 5 % by weight of a dispersant or plasticizer, if necessary; and optionally up to about 30 % by weight of an opacifier or colorant.

WO 02/26196 A1

TOOTH COATING COMPOSITION

Background of the Invention

The present invention is directed to a film forming coating for coating teeth. It is a
5 temporary coating which will eventually wear off or may be easily removed when convenient
or desired.

Temporary protective coatings or removable protective coatings are known. For
example, U.S. Patent No. 5,191,014, to Roberts et al., teaches a temporary protective aqueous
coating composition which is applied to the hydrophobic paint work of newly finished motor
10 vehicles, and yet is easily removable. The composition is a copolymer of (meth)acrylic acid,
and a staple monomer, which creates a copolymer coating having a molecular weight of
10,000 to 200,000 that is soluble under alkaline conditions. U.S. Patent No. 5,330,788, to
Roberts, teaches a temporary coating to protect the surface of an article, which coating is
weather resistant but soluble under alkaline conditions and which is a film-forming acrylic
15 polymer. U.S. Patent No. 5,916,674, to Skelly, et al., discloses an article having a removable
protective film to protect the activated nature of an activated surface. The film-forming
substance is water soluble, preferably a vinylpyrrolidone and vinyl acetate polymer. U.S.
Patent No. 5,945,462, to Salamon, discloses temporary protective coatings for precision
surfaces such as glass, metals, ceramics, plastic and other materials of construction where the
20 coating is a (meth)acrylate-capped organic prepolymer resin having at least one pendent
hydrophilic group. This film-forming system is dependent on reactive curing of monomers
and prepolymers.

There are patents which teach cosmetically improving and altering the appearance of
teeth, such as U.S. Patent No. 6,036,494, to Cohen, which teaches the use of a Bis-GMA
25 (compound) (bisphenol diglycidylmethacrylate) or a glass ionomer. The coatings are reacted
from monomers and/or prepolymers at the dental surface and can be pigmented. But once
coated, it cannot be removed without using a dental pick or tool to remove the shell coating
from the tooth. U.S. Patent No. 5,980,868, to Homola, et al., discloses a dental delivery
system for the protection of surfaces of teeth. The Homola composition provides a protective
30 coating of fatty/waxy base which functions as a transfer agent or barrier stratum, but it does
not appear to be a temporary removable coating. U.S. Patent No. 4,512,743, to Santucci et al.,
teaches a polymerizable composition which can be applied to the surface of teeth, but it
requires the etching of the tooth surface before applying the coating. U.S. Patent No.
4,883,534, and U.S. Patent No. 4,496,322, both to Sandham, et al., teach a varnish containing

a dentally acceptable antimicrobial agent which can be painted on teeth to give a transparent, translucent or tooth colored film which is effectively invisible but provides sustained release of the antimicrobial agent. This is a film which is used to treat infection and can be removed by the application of the liquid varnish base. U.S. Patent No. 5,430,074, to Barnes, et al., teaches a dental restoration kit which provides a gum-colored dental composite for restoring cavities and shorten the appearance of clinical crown on the facial surface of a tooth. The composition is a methacrylate resin. The components are presented separately in a kit for combination and application to the tooth. The composition is reactive and is not considered a temporary removable composition. U.S. Patent No. 4,032,627, to Suchan, et al., teaches a tooth whitening cosmetic composition that is applied temporarily and then removed with solvent. An alkaline solution is necessary for removal. U.S. Patent No. 4,648,845, to Orlowski et al., teaches a method for indirect bonding of chemically or light curable resin-based restoratives such as acrylates and methacrylates to the base metal of dental cast restorations. The composition of Orlowski is not intended to be a temporary removable coating.

While the prior art coatings in general can be easily strippable, they are not suggested for use on teeth, and the coatings that are used for teeth which are removable require special tools or compositions to subsequently remove the coatings. The prior art coatings have been created from reactive monomers, prepolymers, and where necessary, highly reactive initiators like organic peroxides and light sensitive compounds. Any substantially reactive chemical system has the ability to affect the normal chemistry of living tissue and produce unsafe, unwanted, and sometimes toxic and detrimental changes. Likewise, the solvent systems described have included generally toxic compounds including reactive species. The prior art coatings have also been subject to removal or degradation by changes in acid/base balance, most notably toward basic conditions. Acidic and basic conditions are both found in day-to-day activities including eating and tooth brushing. When the conditions of film removal are found in common activities, the film is subject to premature and possibly unexpected and embarrassing removal.

Summary of the Invention

The present invention is to a temporary or removable film forming composition for coating teeth which is a mixture of a natural or synthetic film forming polymer, a solvent, a rheology modifier, a dispersant or plasticizer, if necessary, and optionally an opacifier or colorant. It is applied to teeth preferably by brushing it on the tooth surface. The user can

create temporary colors for the teeth or cover blemished or off color teeth. When the coating is no longer desired, it is readily stripped off. The film-forming system contained herein has several advantages over the cited prior art.

The film-forming system of the present invention comprises orally acceptable ingredients, which, individually, are described in the "Handbook of Pharmaceutical Excipients, 2nd ed". The compounds of the present invention are acceptable and preferred for their demonstrated safety in pharmaceutical preparations. They also produce a film that shows no water solubility invariant of acid/base changes and which has a useful durability as a temporary and removable film. The present invention is a product that gives an aesthetically pleasing coating that is safe in its intended use, shows good performance over a planned duration, and is easily and safely removable when desired.

Detailed Description of the Invention

The present invention is a film forming composition for coating teeth which is a mixture of a film forming polymer; a solvent; a rheology modifier; a dispersant or plasticizer, if necessary; and optionally an opacifier or colorant.

Film formers may be any of the natural polymers including commonly used gums, resins, exudates, animal rendering products and byproducts, such as gelatin and keratin, plant extracts, alginates, cellulose, galactomannans, bacterial products, such as Xanthan gum, and derivatives of these natural polymers, including methyl-, hydroxypropyl-, acetate phthalate, acetate, methoxy, hydroxypropoxy, acetyl, phthalyl, hydrolysates, and salts (Li, Na, K, Ca, Mg, Al, Zn, B, Fe, Cu, Ni), or combinations thereof or associated reaction byproducts. They may also be synthetic polymers, including homopolymers, copolymers, interpolymers, block polymers, or graft polymers, either crosslinked or substantially linear, derived from monomers known to film forming arts such as (meth)acrylic acid homo- and copolymers, including those to be found in U.S. Patents 2,798,053; 3,940,351; 5,034,486; 5,034,487; 5,034,488; 4,062,817; 3,940,351; 2,340,110; 2,340,111; 2,533,635; the disclosures of which are incorporated herein by reference; and which are directed mainly at olefinically unsaturated moieties of various functionality and substitution. The film forming polymer is preferably an acrylic or methacrylic, i.e., (meth)acrylic acid polymer or copolymer, including acrylic acid, methyl acrylate, ethyl acrylate, methacrylic acid, methyl methacrylate, ethyl methacrylate, etc. A preferable acrylic polymer is available from Rohm Pharma GmbH as Eudragit RS 100 and it is the salt of a copolymer of ethyl acrylate, methyl methacrylate, and trimethyl ammonioethylmethacrylate. Other polymers that could be used include ethylcellulose,

polyvinyl acetate, aminoalkyl methacrylate copolymer, chitin, chitosan, wax-type coatings, and the like. Another film forming polymer is Acrycoat acrylic and methacrylic polymers from Corel Pharma-Chem, Ahmedabad, India. What is important is that the polymer is appropriate for use in a mouth and forms a film, has sufficient strength, adheres, and can be subsequently removed. The film former is present in an amount of about 1% to about 30% by weight based upon the weight of the total mixture, although an amount of 5 to 20% by weight is preferred, with about 10% being further preferred.

Any solvent deemed suitable for the desired application/substrate may be used. This includes considerations of cost, color, ease of application, toxicology, environmental impact, regulatory status, effect on film formation and finished properties such as gloss, levelling, taste, flexibility, surface hardness, tensile strength, modulus, abrasion resistance, stain resistance, porosity, release/retention/absorption of target compounds, adhesion, cohesion, and ease of removal, e.g., methanol, ethanol, isopropanol, butanol, water, methylene glycol, ethylene glycol, propylene glycol, butylene glycol, neopentyl glycol, hexylene glycol, acetone, methyl ethyl ketone, ethyl acetate, butyl acetate, cyclohexanone, cyclohexane, methylene chloride, chloroform, carbon tetrachloride, trichloroethylene, perchloroethylene, methyl glycol acetate, toluene, benzene, diethyl ether, benzyl alcohol, and glycerin. The solvent is present in an amount of about 10% to about 99.5% by weight based upon the total weight of the mixture, although about 60% to about 90% by weight based upon the weight of the total mixture is preferred, with an amount of 80% by weight being further preferred.

The rheology modifier is selected to adjust the flow properties of the mixture so that it will remain on a vertical surface without running or creeping. The rheology modifier can be any of the known inorganic rheology modifiers such as clays, such as laponite, bentonite, and the like, and thickener grade silicas, which are well known for use in paints and coatings, commonly used gums, resins, exudates, animal rendering products and byproducts, such as gelatin or keratin, plant extracts, alginates, cellulose, galactomannans, bacterial products, such as Xanthan gum, and derivatives these compositions, including methyl-, hydroxypropyl-, acetate phthalate, acetate, methoxy, hydroxypropoxy, acetyl, phthalyl, hydrolysates, or salts (Li, Na, K, Ca, Mg, Al, Zn, B, Fe, Cu, Ni), or combinations thereof. They may also be synthetic polymeric rheology modifiers, including homopolymers, copolymers, interpolymers, block polymers, and graft polymers, either crosslinked or substantially linear, derived from monomers known to those skilled in rheology modification such as (meth)acrylic acid homo- and copolymers, including those to be found in U.S. Patents 2,798,053; 3,940,351; 5,034,486; 5,034,487; 5,034,488; 4,062,817; 3,940,351; 2,340,110;

2,340,111; 2,533,635. A preferred rheology modifier is 2-hydroxypropyl cellulose. Other rheology modifiers could include crosslinked acrylic acid polymer and copolymers, such as Carbopol polymer from Noveon Inc. and Acrypol polymers from Corel Pharma-Chem, and the S-1700-L series of polymers from SNP, Inc. The rheology modifier is present in an amount of about 0.01% to about 40% by weight based upon the weight of the total mixture, although an amount of 1% by weight is preferred.

The dispersants may be chosen from many known in the arts concerned with particulate dispersion, particularly pigment dispersion, where compatible with the desired application and/or substrate. A dispersant or plasticizer may not be necessary if the polymer allows for the mixing and dispersion of the ingredients. Usually, this is not the case, but it will depend upon the polymer chosen. They may also be selected for reasons described in the choice of solvents above. e.g. sodium lauryl sulfate, polyoxyethylene alkyl ethers, polyoxyethylene castor oil derivatives, polyoxyethylene sorbitan fatty acid esters, polyethylene glycols (PEG), polypropylene glycols (PPG), polyethylene-polypropylene copolymers/block polymers (PEG/PPG), unsaturated polyoxyethylene ethers, silicone copolyols, perfluoroalkyl copolyols. The dispersant is present in an amount of about 0.01% to about 5% by weight based upon the weight of the total mixture, with an amount of 0.5% by weight being further preferred.

Plasticizers can be added specifically for the purpose of film property modification or may be added primarily for other functions including solvent, dispersant, or another film former. These additives are well known in the plastic and film forming arts, e.g., PEG, PPG, PEG/PPG, phthalic esters, phosphoric esters, esters of adipic, azelaic, glutaric or sebacic acid, fatty acid esters or pentaerythritol and their epoxides, citric esters, esters of acetic, propionic or butyric acid, esters of ethylbutyric or ethyl hexanoic acid, glycol esters, benzoic esters, trimellitic esters, sulfonic esters, sulfonamides, anilides, alcohols, ethers, ketones, and abietic derivatives. The dispersant is present in an amount of about 0.01% to about 5% by weight based upon the weight of the total mixture, although an amount of 0.5% by weight is preferred.

Colorants or opacifiers may include both soluble and insoluble compounds and their mixtures known to the arts concerned with coloring, e.g., titanium dioxide, iron oxides and their hydrates, carbon blacks, talc, clays, dyes, lakes, gold and various pigments. The colorant or opacifier is present in an amount of about 0% (i.e., none) to about 30% by weight based upon the weight of the total mixture, although an amount of about 1 to about 10% by weight is preferred. The colorant can be such as would match the surrounding teeth or could be in a

non-tooth color, such as colors for athletic events, holidays, temporary gold teeth or glow-in-the-dark colors.

Additionally, compounds can be added specifically to promote other desirable qualities of the in-process product, finished product, or its resultant film. It is also possible to realize similar qualities from multi-functional ingredients added for other primary benefits. Such desirable qualities may include considerations listed in the choice of solvents above.

The composition of the present invention is primarily for use as a tooth coating, though it could be used as a protective barrier, a diffusion limiting, controlled release coating, a carrier for a drug substance, a low-concentration, long-duration bleaching or surface treating agent, an antimicrobial (chlorhexidines), or some similar application.

The composition is applied by spraying, brushing, or other convenient coating process. The process is not critical, although brushing is the most practical and is preferred. Although the application devices is not critical, one convenient way of applying the composition would be a tube having a wicking device to deliver the coating to a tip which protrudes from the tube. The tip is then pressed against the tooth to deliver the coating. This type of device is similar to a "magic marker". Other devices include a container and brush similar to that for nail polish and the felt pads used for applying make-up.

The coating of the present invention is used as a cosmetic covering over undesirable appearing teeth. It can be applied to the surface of the tooth, but is not a permanent correction because it can be easily removed. It can be used to cover the surfaces of the teeth or to cover old and discolored fillings, or to cover the dark margins of crowns due to gum recession, or to coat crowns that no longer match so that the crown does not have to be replaced. It can also be used to cover a tooth that has a gray appearance due to root canal therapy or large amalgam fillings. The coating of the present invention does not alter the tooth in any way, except the color, and it is reversible. It is designed to be affordable because it does not require a licensed professional for bleaching, bonding, crowns, or veneers. Although not necessary, if desired, the surface of the tooth could be etched using a citric acid wash or a phosphoric acid (33% concentration) treatment (if done professionally by a dentist) to promote greater adhesion and a longer retention time.

The following example is illustrative of the present invention, and should not limit the scope of the invention.

Example 1:

Ingredient	wt. %	Function
Ethanol	79.10	Solvent/Preservative
5 Eudragit RS 100	10.00	Film Former/Rheology Modifier
Klucel HF Pharm	00.60	Rheology Modifier/Film Former
Tween 80	00.30	Dispersant/Plasticizer
Titanium Dioxide	10.00	Opacifier/Colorant
Total:	100.00	

Preparation:

1. (optional) Freeze grind Eudragit to a powdered form to facilitate its dissolution.
2. Dissolve Eudragit into ethanol.
3. Add Tween 20 to the Eudragit solution and disperse TiO₂ in the same under high
15 shear conditions (rotor-stator, colloid mill, ball mill, etc.). This may be done prior to step 1.
where the shear necessary is detrimental to the film former(s).
4. Disperse Klucel into the Eudragit solution and mix at moderate shear (marine
impeller, etc.) to fully dissolve and extend the Klucel.

Removal of the film coating may be easily and safely effected using a solution of 70%
20 ethanol, or of similar composition as the original carrier solvent medium. This allows the
removal of the film under controlled and mild conditions not likely to be found day-to-day in
the oral cavity thus preventing its premature removal. The film in Example 1 has endured
without significant change for four days, at which time it was easily removed in about one
minute cleanly and completely with an 80% solution of ethanol in water.

Description of Selected Ingredients:

Ingredient	Description	Source
Eudragit RS 100	A salt of a copolymer of ethylacrylate, methylmethacrylate and trimethylammonioethylmethacrylate (EA:MA:TMAEMA = 1:2:0.1); MW = 150,000	Rohm Pharm GmbH
Klucel HF Pharm	2-hydroxypropyl cellulose	Aqualon
Tween 80	Polyoxyethylene sorbitan monoleate	ICI

The foregoing embodiments of the present invention have been presented for the purposes of illustration and description. These descriptions and embodiments are not intended to be exhaustive or to limit the invention to the precise form disclosed, and obviously many modifications and variations are possible in light of the above disclosure.

- 5 The embodiments were chosen and described in order to best explain the principle of the invention and its practical applications to thereby enable others skilled in the art to best utilize the invention in its various embodiments and with various modifications as are suited to the particular use contemplated. It is intended that the invention be defined by the following claims.

What we claim is:

1. A film forming composition for coating teeth comprising the following:
 - A) about 0.5 % to about 30% by weight, based upon the weight of the composition, of a film forming polymer;
 - B) about 10% to about 99.5% by weight, based upon the weight of the composition, of solvent;
 - C) about 0.01% to about 40% by weight, based upon the weight of the composition, of a rheology modifier; and
 - D) optionally up to about 30% by weight, based upon the weight of the composition, of an opacifier or colorant.
2. The composition of claim 1 wherein the film forming polymer is selected from the group consisting of natural and synthetic polymers.
3. The composition of claim 1 wherein the film forming polymer is a (meth)acrylate copolymer.
4. The composition of claim 1 wherein the film forming polymer is a salt of a copolymer of ethylacrylate, methylmethacrylate and trimethylammonioethylmethacrylate.
5. The composition of claim 1 wherein the film forming polymer is present in an amount of about 1% to about 20.0% by weight.
6. The composition of claim 1 which further includes a dispersant or plasticizer.
7. The composition of claim 1 which further includes a dispersant or plasticizer in an amount of about 0.01% to about 15% by weight, based upon the weight of the composition.
8. The composition of claim 7 wherein the dispersant is polyoxyethylene sorbitan monoleate.

9. The composition of claim 7 wherein the dispersant or plasticizer is present in an amount of about 0.1% to about 5.0% by weight.
10. The composition of claim 1 wherein the solvent is ethanol.
11. The composition of claim 1 wherein the solvent is present in an amount of about 60.0% to about 80.0% by weight
12. The composition of claim 1 wherein the rheology modifier is hydroxy propyl cellulose.
13. The composition of claim 1 wherein the rheology modifier is present in an amount of about 0.05% to about 40.0% by weight
14. The composition of claim 1 wherein the opacifier is titanium dioxide.
15. The composition of claim 1 wherein the opacifier or colorant is present in an amount of about 0.01% to about 30% by weight.

INTERNATIONAL SEARCH REPORT

Inter nal Application No

PCT/US 01/42120

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61K6/00 A61K6/083 A61K6/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 404 558 A (YISSUM RES DEV CO ; PERIO PROD LTD (IL)) 27 December 1990 (1990-12-27) page 9, line 21 - line 23 tables XX, XXV claims	1-11, 13, 15
X	EP 1 027 877 A (KAO CORP) 16 August 2000 (2000-08-16) paragraph '0027! - paragraph '0031! claims	1-3, 5, 10-15
X	US 4 032 627 A (SUCHAN JOSEPH T ET AL) 28 June 1977 (1977-06-28) cited in the application Formulae I, II claims	1-3, 5, 10-15
	--- -/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

11 March 2002

Date of mailing of the international search report

20/03/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Thornton, S

INTERNATIONAL SEARCH REPORT

Internal Application No
PCT/US 01/42120

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	EP 1 112 750 A (SATO PHARMA ;SUNTORY LTD (JP)) 4 July 2001 (2001-07-04) paragraphs '0017!', '0018!', '0021!', '0023!', '0026! claims -----	1-7, 9, 11-15
E	EP 1 138 308 A (HANIX CO LTD) 4 October 2001 (2001-10-04) paragraph '0025! examples claims -----	1-3, 5, 10-13, 15

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/42120

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0404558	A	27-12-1990	US 5330746 A	19-07-1994
			US 5160737 A	03-11-1992
			AU 631655 B2	03-12-1992
			AU 5766790 A	17-01-1991
			CA 2019410 A1	21-12-1990
			EP 0404558 A1	27-12-1990
			IL 94749 A	24-01-1995
			JP 3128316 A	31-05-1991
			US 5438076 A	01-08-1995
			US 5648399 A	15-07-1997
			US 5639795 A	17-06-1997
EP 1027877	A	16-08-2000	JP 11092350 A	06-04-1999
			EP 1027877 A1	16-08-2000
			WO 9915131 A1	01-04-1999
US 4032627	A	28-06-1977	GB 1434081 A	28-04-1976
EP 1112750	A	04-07-2001	EP 1112750 A1	04-07-2001
			CN 1320046 T	31-10-2001
			WO 0103742 A1	18-01-2001
EP 1138308	A	04-10-2001	JP 2001278725 A	10-10-2001
			AU 3135401 A	04-10-2001
			EP 1138308 A2	04-10-2001
			US 2001037750 A1	08-11-2001

BEST AVAILABLE COPY